

## UT Pro Wall-Washer

09.7500.40 - White

Wall-Washer lighting module to be installed in Tracking Power profile with LED light source. 220-240V power supply integrated. .40 versions come with the track adapter, the arm and the rear of the head in black.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1706
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	25.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Asymmetric
<b>Optical type</b>	Wall Washer
	Down
<b>Beam angle (°)</b>	36
<b>Beam angle C90-270 (°)</b>	75



<b>Beam Angle:</b>	36°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	1199	0.78	
2	300	1.56	
3	133	2.34	
4	75	3.12	
5	48	3.90	

Luminous flux luminaire  
1706 lm



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		

### Physical

<b>Color</b>	White	<b>Length (mm)</b>	420
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	1.05		
<b>Tilt (°)</b>	15		
<b>Rotation (°)</b>	360		

