

UT Pro Wall-Washer

■ 09.7501.14 - Black

Wall-Washer lighting module to be installed in Tracking Power profile with LED light source. 220-240V power supply integrated.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1700 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 25.5W | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-------------|
| Lighting type | Direct |
| LED type | Top LED |
| Light distribution | Asymmetric |
| Optical type | Wall Washer |
| | Down |
| Beam angle (°) | 36 |
| Beam angle C90-270 (°) | 75 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 36° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 1184 | 0.76 | |
| 2 | 296 | 1.52 | |
| 3 | 132 | 2.28 | |
| 4 | 74 | 3.04 | |
| 5 | 47 | 3.80 | |

Luminous flux luminaire
1700 lm



Electrical

| | | | |
|-----------------------|--------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |

Physical

| | | | |
|---------------------|------------|--------------------|-----|
| Color | Black | Length (mm) | 420 |
| Orientation | Adjustable | | |
| Weight (kg) | 1.05 | | |
| Tilt (°) | 15 | | |
| Rotation (°) | 360 | | |

