


UT Pro Wall-Washer Dali Version GA-600

■ 09.7504.14.DA - Black

Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. DALI version requires dimmable tracks (please refer to the "Tracks" chapter).




Main specifications

Number of heads	1	Mountings	Track
Lamp category	LED	Environment	Indoor dry location
Power (W)	25.2W		
System power (W)	25.5		
Net lumen (lm)	1554		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Asymmetric
Optical type	Wall Washer
Beam angle (°)	36
Beam angle C90-270 (°)	75



Beam Angle: 36°

h(m) E(lx) D(m)

1 1083 0.76

2 271 1.52

3 120 2.28

4 68 3.04

5 43 3.80

Luminous flux luminaire
1554 lm

Electrical

Frequency (Hz)	50/60	Driver type	Non Dimmable, Dimmable DALI
Voltage (V)	220-240V		1
Current (mA)	700	Emergency	Without
Dimmable	Yes	Insulation class	I
Driver	Integrated		

Physical

Color	Black	Length (mm)	420
Orientation	Adjustable		
Weight (kg)	1.05		
Tilt (°)	15		
Rotation (°)	360		

