


UT Pro Wall-Washer Dali Version GA-600

09.7505.40.DA - White

Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. DALI version requires dimmable tracks (please refer to the "Tracks" chapter). .40 versions come with the track adapter, the arm and the rear of the head in black.




Main specifications

Number of heads	1	Environment	Indoor
Lamp category	LED		
Power (W)	25.2W		
Net lumen (lm)	1700		
Mountings	Track		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Asymmetric
Optical type	Wall-washer
Beam angle (°)	36
Beam angle C90-270 (°)	75



Beam Angle:	36°		
h(m)	E(lx)	D(m)	
1	1184	0.76	
2	296	1.52	
3	132	2.28	
4	74	3.04	
5	47	3.80	

Luminous flux luminaire
1700 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic, Electronic dimmable DALI		

Certification / Marking



Physical

Color	White	Length (mm)	420
Orientation	Adjustable		
Weight (kg)	1.05		
Tilt (°)	15		
Rotation (°)	360		