


UT Pro Wall-Washer Dali Version GA-600 All White

■ 09.7504.40.YU - White

Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. DALI version requires dimmable tracks (please refer to the "Tracks" chapter). In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. DALI version requires dimmable tracks (please refer to the "Tracks" chapter). In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.




Main specifications

Number of heads	1	Mountings	Track
Lamp category	LED	Environment	Indoor dry location
Power (W)	25.2W		
System power (W)	25.5		
Net lumen (lm)	1554		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Asymmetric
Optical type	Wall Washer
	Down
Beam angle (°)	36
Beam angle C90-270 (°)	75



Beam Angle:	36°		
	h(m)	E(lx)	D(m)
1	1199	0.78	
2	300	1.56	
3	133	2.34	
4	75	3.12	
5	48	3.90	

Luminous flux luminaire
1706 lm

Electrical

Frequency (Hz)	50/60	Driver type	Non Dimmable, Dimmable DALI
Voltage (V)	220-240V		1
Current (mA)	700	Emergency	Without
Dimmable	Yes	Insulation class	I
Driver	Integrated		

Physical

Color	White	Length (mm)	420
Orientation	Adjustable		
Weight (kg)	1.05		
Tilt (°)	15		
Rotation (°)	360		

