





## 09.7505.40 - White

Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. .40 versions come with the track adapter, the arm and the rear of the head in black.

## Main specifications

| Number of heads  | 1     | CRI            | 90                  |
|------------------|-------|----------------|---------------------|
| Lamp category    | LED   | Net lumen (lm) | 1700                |
| Power (W)        | 25.2W | Mountings      | Track               |
| System power (W) | 25.5  | Environment    | Indoor dry location |

4000K

CCT (K)

Optical

Lighting type LED type Light distribution Optical type

Beam angle (°) Beam angle C90-270 (°)

Direct Top LED Asymmetric Wall Washer Down 36 75

> 300 1184 cd Luminous flux luminaire 1700 lm

Beam Angle: 36° h(m) E(Ix)D(m) 1184 0.76 1 2 1.52 296 3 132 2.28 4 3.04 74 5 47 3.80



Frequency (Hz) 50/60 220-240V Voltage (V) Current (mA) 700 Dimmable No Driver Integrated Driver type **Emergency** Insulation class

Length (mm)

Non Dimmable Without

420



Color White Orientation Weight (kg) 1.05 Tilt (°) 15 Rotation (°) 360

Adjustable



