

## UT Pro Wall-Washer GA-69 All White

09.7504.40.78 - White/White

Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.


Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1706
Power (W)	25.2W	Mountings	Track
System power (W)	25.5	Environment	Indoor dry location
CCT (K)	3000K		

### Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Asymmetric
Optical type	Wall Washer
	Down
Beam angle (°)	36
Beam angle C90-270 (°)	75



Beam Angle: 36°

h(m)	E(lx)	D(m)
1	1199	0.78
2	300	1.56
3	133	2.34
4	75	3.12
5	48	3.90

Luminous flux luminaire  
1706 lm

### Electrical

Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	220-240V	Emergency	Without
Current (mA)	700	Insulation class	I
Dimmable	No		
Driver	Integrated		

### Physical

Color	White/White	Length (mm)	420
Orientation	Adjustable		
Weight (kg)	1.05		
Tilt (°)	15		
Rotation (°)	360		

