

UT Pro Wall-Washer GA-69 All White

09.7505.40.78 - White/White

Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.


Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1700
Power (W)	25.2W	Mountings	Track
System power (W)	25.5	Environment	Indoor dry location
CCT (K)	4000K		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Asymmetric
Optical type	Wall Washer
	Down
Beam angle (°)	36
Beam angle C90-270 (°)	75



Beam Angle: 36°

h(m) E(lx) D(m)

1	1184	0.76
2	296	1.52
3	132	2.28
4	74	3.04
5	47	3.80

Luminous flux luminaire
1700 lm

Electrical

Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	220-240V	Emergency	Without
Current (mA)	700	Insulation class	I
Dimmable	No		
Driver	Integrated		

Physical

Color	White/White	Length (mm)	420
Orientation	Adjustable		
Weight (kg)	1.05		
Tilt (°)	15		
Rotation (°)	360		

