

UT Spot Ceiling Ø 57

■ 09.4460.30A - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	CRI	80
Lamp category	LED	Net lumen (lm)	1255
Power (W)	23.2	Mountings	Ceiling surface
System power (W)	23.2	Environment	Indoor dry location
CCT (K)	3000K		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Beam Angle: 10°

	h(m)	E(lx)	D(m)
1	14650	0.18	
2	3662	0.36	
3	1628	0.54	
4	916	0.72	
5	586	0.90	

Luminous flux luminaire
1255 lm



Electrical

Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	220-240V	Emergency	Without
Current (mA)	550	Insulation class	II
Dimmable	No		
Driver	Remote included		

Physical

Color	White	Spot diameter (mm)	57
Orientation	Adjustable		
Weight (kg)	0.59		
Tilt (°)	90		
Rotation (°)	360		



Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory.

UT Spot Ceiling Ø 57



Snoot shielding cone
08.0526.00



Elliptical lens
08.8431.00



Snoot shielding cone
08.0526.BW



Snoot shielding cone
08.0526.40



Screening crosspiece
08.8429.00



Flood lens
08.8432.00



Honeycomb
08.8428.00