

UT Spot Ceiling Ø 57■ **09.4464.14A - Black**


Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.

**Main specifications**

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	941
Power (W)	23.2	Mountings	Ceiling surface
System power (W)	23.2	Environment	Indoor dry location
CCT (K)	3000K		


Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	21
Beam angle C90-270 (°)	21



Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5178	0.37
2	1294	0.73
3	575	1.10
4	324	1.47
5	207	1.83

Luminous flux luminaire
941 lm**Electrical**


Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	220-240V	Emergency	Without
Current (mA)	550	Insulation class	II
Dimmable	No		
Driver	Remote included		

Physical

Color	Black	Spot diameter (mm)	57
Orientation	Adjustable		
Weight (kg)	0.59		
Tilt (°)	90		
Rotation (°)	360		

Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory.




UT Spot Ceiling Ø 57



Flood lens
08.8432.00

Honeycomb
08.8428.00

Screening crosspiece
08.8429.00



Snoot shielding cone
08.0526.00

Elliptical lens
08.8431.00

Snoot shielding cone
08.0526.BW



Snoot shielding cone
08.0526.40