

## UT Spot Ceiling Ø 57

■ 09.4464.30A - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




## Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 941                 |
| Power (W)        | 23.2  | Mountings      | Ceiling surface     |
| System power (W) | 23.2  | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |


## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 21        |
| Beam angle C90-270 (°) | 21        |



Beam Angle: 21°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 5178  | 0.37 |
| 2    | 1294  | 0.73 |
| 3    | 575   | 1.10 |
| 4    | 324   | 1.47 |
| 5    | 207   | 1.83 |

Luminous flux luminaire  
941 lm

## Electrical


|                |                 |                  |              |
|----------------|-----------------|------------------|--------------|
| Frequency (Hz) | 50/60           | Driver type      | Non Dimmable |
| Voltage (V)    | 220-240V        | Emergency        | Without      |
| Current (mA)   | 550             | Insulation class | II           |
| Dimmable       | No              |                  |              |
| Driver         | Remote included |                  |              |

## Physical

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | White      | Spot diameter (mm) | 57 |
| Orientation  | Adjustable |                    |    |
| Weight (kg)  | 0.59       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

## Note


Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory.



UT Spot Ceiling Ø 57



Snoot shielding cone  
08.0526.00



Elliptical lens  
08.8431.00



Snoot shielding cone  
08.0526.BW



Snoot shielding cone  
08.0526.40



Screening crosspiece  
08.8429.00



Flood lens  
08.8432.00



Honeycomb  
08.8428.00