

UT Spot Ceiling Ø 57

■ 09.4472.14A - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	1216
Lamp category	LED	Mountings	Ceiling surface
Power (W)	23.5W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		


Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	42
Beam angle C90-270 (°)	42



Beam Angle:	42°		
	h(m)	E(lx)	D(m)
	1	2879	0.76
	2	720	1.52
	3	320	2.28
	4	180	3.05
	5	115	3.81

Luminous flux luminaire
1216 lm



Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	0.83
Tilt (°)	90
Rotation (°)	360



Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory.

UT Spot Ceiling Ø 57



Screening crosspiece
08.8429.00



Snoot shielding cone
08.0526.40



Snoot shielding cone
08.0526.BW



Elliptical lens
08.8431.00



Snoot shielding cone
08.0526.00



Honeycomb
08.8428.00



Flood lens
08.8432.00