

## UT Spot Ceiling Ø 57

09.4472.30A - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1216
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	23.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	90		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	42
<b>Beam angle C90-270 (°)</b>	42



<b>Beam Angle:</b>	42°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	2879	0.76	
2	720	1.52	
3	320	2.28	
4	180	3.05	
5	115	3.81	

Luminous flux luminaire  
1216 lm



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.83
<b>Tilt (°)</b>	90
<b>Rotation (°)</b>	360



### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory.

## UT Spot Ceiling Ø 57



---

Elliptical lens  
08.8431.00



---

Honeycomb  
08.8428.00



---

Flood lens  
08.8432.00



---

Snoot shielding cone  
08.0526.00



---

Snoot shielding cone  
08.0526.40



---

Snoot shielding cone  
08.0526.BW



---

Screening crosspiece  
08.8429.00