

## UT Spot Ceiling Ø 57 Dali Version

■ 09.4461.14ADA - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1184
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	21.5W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	21
<b>Beam angle C90-270 (°)</b>	21



<b>Beam Angle:</b>	21°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
	1	6515	0.37
	2	1629	0.73
	3	724	1.10
	4	407	1.47
	5	261	1.83

Luminous flux luminaire  
1184 lm



### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic dimmable DALI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.83
<b>Tilt (°)</b>	90
<b>Rotation (°)</b>	360

### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory.



## UT Spot Ceiling Ø 57 Dali Version



---

Snoot shielding cone  
08.0526.BW



---

Snoot shielding cone  
08.0526.40




---

Honeycomb  
08.8428.00



---

Screening crosspiece  
08.8429.00



---

Elliptical lens  
08.8431.00



---

Flood lens  
08.8432.00



---

Snoot shielding cone  
08.0526.00