

UT Spot Ceiling Ø 86**■ 09.4263.14 - Black**


Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.

**Main specifications**

Number of heads	1	CRI	98
Lamp category	LED	Net lumen (lm)	1822
Power (W)	34.1W	Mountings	Ceiling surface
System power (W)	34.1	Environment	Indoor dry location
CCT (K)	3000K		


Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle: 16°

h(m)	E(lx)	D(m)
1	13803	0.28
2	3451	0.55
3	1534	0.83
4	863	1.10
5	552	1.38

Luminous flux luminaire
1822 lm**Electrical**

Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	220-240V	Emergency	Without
Current (mA)	1000	Insulation class	II
Dimmable	No		
Driver	Remote included		

Physical

Color	Black	Rotation (°)	360
Orientation	Adjustable	Spot diameter (mm)	86
Recessed depth (mm)	62		
Weight (kg)	1.36		
Tilt (°)	90		



UT Spot Ceiling Ø 86



Screening crosspiece
08.8411.00

Holding ring
08.8410.00