


## UT Spot Ceiling Ø 86

■ 09.4264.14A - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1898
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	34.1W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	98		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	23
<b>Beam angle C90-270 (°)</b>	23



<b>Beam Angle: 23°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	8820	0.41
2	2205	0.82
3	980	1.23
4	551	1.64
5	353	2.05


Luminous flux luminaire  
1898 lm

### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable	<b>Spot diameter (mm)</b>	86
<b>Recessed depth (mm)</b>	62		
<b>Weight (kg)</b>	1.36		
<b>Tilt (°)</b>	90		



## UT Spot Ceiling Ø 86



---

Holding ring  
08.8410.00



---

Screening crosspiece  
08.8411.00