


## UT Spot Ceiling Ø 86

■ 09.4270.14 - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2216
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	29.3W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	80		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	17
<b>Beam angle C90-270 (°)</b>	17



<b>Beam Angle:</b>	17°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
	1	16217	0.29
	2	4054	0.58
	3	1802	0.88
	4	1014	1.17
	5	649	1.46


Luminous flux luminaire  
2216 lm

### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	62		
<b>Weight (kg)</b>	1.36		
<b>Tilt (°)</b>	90		



## UT Spot Ceiling Ø 86



---

Holding ring  
08.8410.00



---

Screening crosspiece  
08.8411.00