UT Spot Ceiling Ø 86

09.4270.14 - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.



Main specifications

Number of heads	1	**CRI**	80
Lamp category	LED	**Net lumen (lm)**	2216
Power (W)	29.3W	**Mountings**	Ceiling surface
System power (W)	29.3	**Environment**	Indoor dry location
CCT (K)	4000K		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	17
Beam angle C90-270 (°)	17



Luminous flux luminaire
2216 lm

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	16217	0.29
2	4054	0.58
3	1802	0.88
4	1014	1.17
5	649	1.46

Electrical

Frequency (Hz)	50/60	**Driver type**	Non Dimmable
Voltage (V)	220-240V	**Emergency**	Without
Current (mA)	1000	**Insulation class**	II
Dimmable	No		
Driver	Remote included		

Physical

Color	Black	**Rotation (°)**	360
Orientation	Adjustable	**Spot diameter (mm)**	86
Recessed depth (mm)	62		
Weight (kg)	1.36		
Tilt (°)	90		

UT Spot Ceiling Ø 86

Screening crosspiece
08.8411.00

Holding ring
08.8410.00