

## UT Spot Ceiling Ø 86

09.4271.30A - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




## Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 80                  |
| Lamp category    | LED   | Net lumen (lm) | 2260                |
| Power (W)        | 29.3W | Mountings      | Ceiling surface     |
| System power (W) | 30    | Environment    | Indoor dry location |
| CCT (K)          | 4000K |                |                     |


## Optical

|                        |              |
|------------------------|--------------|
| Lighting type          | Direct       |
| LED type               | Phosphor LED |
| Light distribution     | Symmetric    |
| Optical type           | Medium       |
| Beam angle (°)         | 23           |
| Beam angle C90-270 (°) | 23           |



Beam Angle: 23°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 0.41 | 10652 |      |
| 2 | 0.81 | 2663  |      |
| 3 | 1.22 | 1184  |      |
| 4 | 1.63 | 666   |      |
| 5 | 2.03 | 426   |      |


Luminous flux luminaire  
2260 lm

## Electrical

|                |                 |                  |              |
|----------------|-----------------|------------------|--------------|
| Frequency (Hz) | 50/60           | Driver type      | Non Dimmable |
| Voltage (V)    | 220-240V        | Emergency        | Without      |
| Current (mA)   | 1000            | Insulation class | II           |
| Dimmable       | No              |                  |              |
| Driver         | Remote included |                  |              |

## Physical

|                     |            |                    |     |
|---------------------|------------|--------------------|-----|
| Color               | White      | Rotation (°)       | 360 |
| Orientation         | Adjustable | Spot diameter (mm) | 86  |
| Recessed depth (mm) | 62         |                    |     |
| Weight (kg)         | 1.36       |                    |     |
| Tilt (°)            | 90         |                    |     |



UT Spot Ceiling Ø 86



---

Screening crosspiece  
08.8411.00

---

Holding ring  
08.8410.00