

UT Spot Ceiling Ø 86

■ 09.4272.14 - Black


Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.

**Main specifications**

Number of heads	1	CRI	80
Lamp category	LED	Net lumen (lm)	1947
Power (W)	29.3W	Mountings	Ceiling surface
System power (W)	29.3	Environment	Indoor dry location
CCT (K)	4000K		


Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	32
Beam angle C90-270 (°)	32



Beam Angle: 32°

h(m)	E(lx)	D(m)
1	5719	0.58
2	1430	1.15
3	635	1.73
4	357	2.31
5	229	2.89

Luminous flux luminaire
1947 lm**Electrical**

Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	220-240V	Emergency	Without
Current (mA)	1000	Insulation class	II
Dimmable	No		
Driver	Remote included		

Physical

Color	Black	Rotation (°)	360
Orientation	Adjustable	Spot diameter (mm)	86
Recessed depth (mm)	62		
Weight (kg)	1.36		
Tilt (°)	90		



UT Spot Ceiling Ø 86



Holding ring
08.8410.00

Screening crosspiece
08.8411.00