UT Spot Ceiling Ø 86

09.4862.30A - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.



Main specifications

Number of heads	1	**CRI**	80
Lamp category	LED	**Net lumen (lm)**	2408
Power (W)	32.8W	**Mountings**	Ceiling surface
System power (W)	32.8	**Environment**	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	37
Beam angle C90-270 (°)	37



Luminous flux luminaire
2408 lm

Beam Angle: 37°

h(m)	E(lx)	D(m)
1	6735	0.67
2	1684	1.34
3	748	2.01
4	421	2.69
5	269	3.36

Electrical

Frequency (Hz)	50/60	**Driver type**	Non Dimmable
Voltage (V)	220-240V	**Emergency**	Without
Current (mA)	900	**Insulation class**	II
Dimmable	No		
Driver	Remote included		

Physical

Color	White	**Spot diameter (mm)**	86
Orientation	Adjustable		
Weight (kg)	1.18		
Tilt (°)	90		
Rotation (°)	360		

UT Spot Ceiling Ø 86

Screening crosspiece
08.8411.00

Holding ring
08.8410.00

Flood lens
08.8175.68

Elliptical lens
08.8163.68

Honeycomb
08.8495.14