

## UT Spot Ceiling Ø 86 Dali Version

■ 09.4263.14.DA - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 98                  |
| Lamp category    | LED   | Net lumen (lm) | 1822                |
| Power (W)        | 34.1W | Mountings      | Ceiling surface     |
| System power (W) | 34.1  | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

### Optical


|                        |              |
|------------------------|--------------|
| Lighting type          | Direct       |
| LED type               | Phosphor LED |
| Light distribution     | Symmetric    |
| Optical type           | Spot         |
| Beam angle (°)         | 16           |
| Beam angle C90-270 (°) | 16           |



Beam Angle: 16°

|   | h(m)  | E(lx) | D(m) |
|---|-------|-------|------|
| 1 | 13803 | 0.28  |      |
| 2 | 3451  | 0.55  |      |
| 3 | 1534  | 0.83  |      |
| 4 | 863   | 1.10  |      |
| 5 | 552   | 1.38  |      |

Luminous flux luminaire  
1822 lm




### Electrical

|                |                 |                  |                 |
|----------------|-----------------|------------------|-----------------|
| Frequency (Hz) | 50/60           | Driver type      | Dimmable DALI 1 |
| Voltage (V)    | 220-240V        | Emergency        | Without         |
| Current (mA)   | 1050            | Insulation class | II              |
| Dimmable       | Yes             |                  |                 |
| Driver         | Remote included |                  |                 |

### Physical

|                     |            |                    |     |
|---------------------|------------|--------------------|-----|
| Color               | Black      | Rotation (°)       | 360 |
| Orientation         | Adjustable | Spot diameter (mm) | 86  |
| Recessed depth (mm) | 62         |                    |     |
| Weight (kg)         | 1.36       |                    |     |
| Tilt (°)            | 90         |                    |     |



UT Spot Ceiling Ø 86 Dali Version



---

Screening crosspiece  
08.8411.00

---

Holding ring  
08.8410.00