



UT Spot Ceiling Ø 86 Dali Version

■ 09.4270.14.DA - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	2216
Lamp category	LED	Mountings	Ceiling surface
Power (W)	29.3W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	17
Beam angle C90-270 (°)	17



Beam Angle: 17°

	h(m)	E(lx)	D(m)
1	16217	0.29	
2	4054	0.58	
3	1802	0.88	
4	1014	1.17	
5	649	1.46	

Luminous flux luminaire
2216 lm

Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		
Emergency	Without		


Physical

Color	Black	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	62		
Weight (kg)	1.36		
Tilt (°)	90		

UT Spot Ceiling Ø 86 Dali Version



Screening crosspiece
08.8411.00



Holding ring
08.8410.00