


UT Spot Ceiling Ø 86 Dali Version

09.4272.30.DA - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	CRI	80
Lamp category	LED	Net lumen (lm)	1947
Power (W)	29.3W	Mountings	Ceiling surface
System power (W)	29.3	Environment	Indoor dry location
CCT (K)	4000K		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	32
Beam angle C90-270 (°)	32



Beam Angle: 32°

h(m)	E(lx)	D(m)
1	5719	0.58
2	1430	1.15
3	635	1.73
4	357	2.31
5	229	2.89


Luminous flux luminaire
1947 lm

Electrical

Frequency (Hz)	50/60	Driver type	Dimmable DALI 1
Voltage (V)	220-240V	Emergency	Without
Current (mA)	1050	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Physical

Color	White	Rotation (°)	360
Orientation	Adjustable	Spot diameter (mm)	86
Recessed depth (mm)	62		
Weight (kg)	1.36		
Tilt (°)	90		



UT Spot Ceiling Ø 86 Dali Version



Screening crosspiece
08.8411.00



Holding ring
08.8410.00