

UT Spot Ceiling Ø 86 Dali Version

■ 09.4863.14ADA - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	2190
Power (W)	32.8W	Mountings	Ceiling surface
System power (W)	32.8	Environment	Indoor dry location
CCT (K)	3000K		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12°
Beam angle C90-270 (°)	12°



Beam Angle: 12°

	h(m)	E(lx)	D(m)
1	28219	0.21	
2	7055	0.41	
3	3135	0.62	
4	1764	0.82	
5	1129	1.03	

Luminous flux luminaire
2190 lm



Electrical

Frequency (Hz)	50/60	Driver type	Dimmable DALI 1
Voltage (V)	220-240V	Emergency	Without
Current (mA)	900	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Physical

Color	Black	Spot diameter (mm)	86
Orientation	Adjustable		
Weight (kg)	1.18		
Tilt (°)	90		
Rotation (°)	360		



UT Spot Ceiling Ø 86 Dali Version



Elliptical lens
08.8163.68

Screening crosspiece
08.8411.00

Honeycomb
08.8495.14



Flood lens
08.8175.68

Holding ring
08.8410.00