


## UT Spot Ceiling Ø 86 Dali Version

09.4865.30ADA - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1991
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	32.8W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	37
<b>Beam angle C90-270 (°)</b>	37



<b>Beam Angle:</b>	37°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	5566	0.67	
2	1392	1.34	
3	618	2.01	
4	348	2.69	
5	223	3.36	

Luminous flux luminaire  
1991 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.66
<b>Tilt (°)</b>	90
<b>Rotation (°)</b>	360



## UT Spot Ceiling Ø 86 Dali Version



---

Honeycomb  
08.8495.14



---

Flood lens  
08.8175.68



---

Holding ring  
08.8410.00



---

Elliptical lens  
08.8163.68



---

Screening crosspiece  
08.8411.00