


UT Spot Ceiling Ø 86 Dali Version

■ 09.4870.14ADA - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 2281 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 32.8W | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 12° |
| Beam angle C90-270 (°) | 12° |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 12° | | |
| | h(m) | E(lx) | D(m) |
| | 1 | 29396 | 0.21 |
| | 2 | 7349 | 0.41 |
| | 3 | 3266 | 0.62 |
| | 4 | 1837 | 0.82 |
| | 5 | 1176 | 1.03 |


Luminous flux luminaire
2281 lm

Electrical

| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical


| | |
|---------------------|------------|
| Color | Black |
| Orientation | Adjustable |
| Weight (kg) | 1.66 |
| Tilt (°) | 90 |
| Rotation (°) | 360 |



UT Spot Ceiling Ø 86 Dali Version



Honeycomb
08.8495.14



Holding ring
08.8410.00



Flood lens
08.8175.68



Screening crosspiece
08.8411.00



Elliptical lens
08.8163.68