


UT Spot Ceiling Ø 86 Dali Version

■ 09.4872.14ADA - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	2074
Lamp category	LED	Mountings	Ceiling surface
Power (W)	32.8W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	37
Beam angle C90-270 (°)	37



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	5799	0.67
2	1450	1.34
3	644	2.01
4	362	2.69
5	232	3.36


Luminous flux luminaire
2074 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	1.66
Tilt (°)	90
Rotation (°)	360



UT Spot Ceiling Ø 86 Dali Version



Flood lens
08.8175.68



Honeycomb
08.8495.14



Elliptical lens
08.8163.68



Holding ring
08.8410.00



Screening crosspiece
08.8411.00