

**UT Spot Ceiling Ø57**

09.4460.30A - White


Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.

**Main specifications**

|                 |       |                |                 |
|-----------------|-------|----------------|-----------------|
| Number of heads | 1     | Net lumen (lm) | 1255            |
| Lamp category   | LED   | Mountings      | Ceiling surface |
| Power (W)       | 21.5W | Environment    | Indoor          |
| CCT (K)         | 3000K |                |                 |
| CRI             | 80    |                |                 |

**Optical**


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 10        |
| Beam angle C90-270 (°) | 10        |



Beam Angle: 10°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 14650 | 0.18 |
| 2    | 3662  | 0.36 |
| 3    | 1628  | 0.54 |
| 4    | 916   | 0.72 |
| 5    | 586   | 0.90 |


Luminous flux luminaire  
1255 lm

**Electrical**

|                |            |                  |    |
|----------------|------------|------------------|----|
| Frequency (Hz) | 50/60      | Insulation class | II |
| Dimmable       | No         |                  |    |
| Driver         | Integrated |                  |    |
| Driver type    | Electronic |                  |    |
| Emergency      | Without    |                  |    |

**Physical**

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 0.83       |
| Tilt (°)     | 90         |
| Rotation (°) | 360        |

**Note**

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory.

UT Spot Ceiling Ø57



---

Honeycomb  
08.8428.00

---

Flood lens  
08.8432.00

---

Elliptical lens  
08.8431.00



---

Snoot shielding cone  
08.0526.00

---

Snoot shielding cone  
08.0526.40

---

Snoot shielding cone  
08.0526.BW



---

Screening crosspiece  
08.8429.00