

UT Spot Ceiling Ø57■ **09.4463.14A - Black**


Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.

**Main specifications**

Number of heads	1	Net lumen (lm)	997
Lamp category	LED	Mountings	Ceiling surface
Power (W)	21.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		


Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Beam Angle: 10°

h(m)	E(lx)	D(m)
1	11643	0.18
2	2911	0.36
3	1294	0.54
4	728	0.72
5	466	0.90

Luminous flux luminaire
997 lm**Electrical**


Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	0.83
Tilt (°)	90
Rotation (°)	360

Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory.



UT Spot Ceiling Ø57



Honeycomb
08.8428.00



Flood lens
08.8432.00



Elliptical lens
08.8431.00



Snoot shielding cone
08.0526.00



Snoot shielding cone
08.0526.40



Snoot shielding cone
08.0526.BW



Screening crosspiece
08.8429.00