

## UT Spot Ceiling Ø57

09.4465.30A - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




## Main specifications

|                 |       |                |                 |
|-----------------|-------|----------------|-----------------|
| Number of heads | 1     | Net lumen (lm) | 1108            |
| Lamp category   | LED   | Mountings      | Ceiling surface |
| Power (W)       | 21.5W | Environment    | Indoor          |
| CCT (K)         | 3000K |                |                 |
| CRI             | 90    |                |                 |


## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 42        |
| Beam angle C90-270 (°) | 42        |



Beam Angle: 42°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2623  | 0.76 |
| 2    | 656   | 1.52 |
| 3    | 291   | 2.28 |
| 4    | 164   | 3.05 |
| 5    | 105   | 3.81 |

Luminous flux luminaire  
1108 lm

## Electrical


|                |            |                  |    |
|----------------|------------|------------------|----|
| Frequency (Hz) | 50/60      | Insulation class | II |
| Dimmable       | No         |                  |    |
| Driver         | Integrated |                  |    |
| Driver type    | Electronic |                  |    |
| Emergency      | Without    |                  |    |

## Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 0.83       |
| Tilt (°)     | 90         |
| Rotation (°) | 360        |

## Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory.



UT Spot Ceiling Ø57



---

Honeycomb  
08.8428.00

---

Flood lens  
08.8432.00

---

Elliptical lens  
08.8431.00



---

Snoot shielding cone  
08.0526.00

---

Snoot shielding cone  
08.0526.40

---

Snoot shielding cone  
08.0526.BW



---

Screening crosspiece  
08.8429.00