


## UT Spot Ceiling Ø86

09.4263.30 - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1822
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	34.1W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	98		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	16
<b>Beam angle C90-270 (°)</b>	16



<b>Beam Angle:</b>	16°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
	1	13803	0.28
	2	3451	0.55
	3	1534	0.83
	4	863	1.10
	5	552	1.38

Luminous flux luminaire  
1822 lm


### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic		


### Physical

<b>Color</b>	White	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	62		
<b>Weight (kg)</b>	1.36		
<b>Tilt (°)</b>	90		

### Certification / Marking



## UT Spot Ceiling Ø86



---

Holding ring  
08.8410.00



---

Screening crosspiece  
08.8411.00