


UT Spot Ceiling Ø86

09.4860.30A - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	2650
Lamp category	LED	Mountings	Ceiling surface
Power (W)	32.8W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12°
Beam angle C90-270 (°)	12°



Beam Angle: 12°

	h(m)	E(lx)	D(m)
1	34142	0.21	
2	8535	0.41	
3	3794	0.62	
4	2134	0.82	
5	1366	1.03	

Luminous flux luminaire
2650 lm


Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote		
Driver type	Electronic		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.66
Tilt (°)	90
Rotation (°)	360

Certification / Marking



UT Spot Ceiling Ø86



Holding ring
08.8410.00



Screening crosspiece
08.8411.00



Elliptical lens
08.8163.68



Flood lens
08.8175.68



Honeycomb
08.8495.14