

## UT Spot Ceiling Ø86

■ 09.4861.14A - Black

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




## Main specifications

|                 |       |                |                 |
|-----------------|-------|----------------|-----------------|
| Number of heads | 1     | Net lumen (lm) | 2528            |
| Lamp category   | LED   | Mountings      | Ceiling surface |
| Power (W)       | 32.8W | Environment    | Indoor          |
| CCT (K)         | 3000K |                |                 |
| CRI             | 80    |                |                 |


## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 24        |
| Beam angle C90-270 (°) | 24        |



Beam Angle: 24°

|   | h(m)  | E(lx) | D(m) |
|---|-------|-------|------|
| 1 | 11472 | 0.43  |      |
| 2 | 2868  | 0.86  |      |
| 3 | 1275  | 1.28  |      |
| 4 | 717   | 1.71  |      |
| 5 | 459   | 2.14  |      |

Luminous flux luminaire  
2528 lm


## Electrical

|                |            |                  |         |
|----------------|------------|------------------|---------|
| Frequency (Hz) | 50/60      | Emergency        | Without |
| Voltage (V)    | 220.00     | Insulation class | II      |
| Dimmable       | No         |                  |         |
| Driver         | Remote     |                  |         |
| Driver type    | Electronic |                  |         |

## Physical

|              |            |
|--------------|------------|
| Color        | Black      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.66       |
| Tilt (°)     | 90         |
| Rotation (°) | 360        |

## Certification / Marking



UT Spot Ceiling Ø86



Holding ring  
08.8410.00



Screening crosspiece  
08.8411.00



Elliptical lens  
08.8163.68



Flood lens  
08.8175.68



Honeycomb  
08.8495.14