


UT Spot Ceiling Ø86 Dali Version

09.4265.30.DA - White

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	1654
Lamp category	LED	Mountings	Ceiling surface
Power (W)	34.1W	Environment	Indoor
CCT (K)	3000K		
CRI	98		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	32
Beam angle C90-270 (°)	32



Beam Angle: 32°

h(m)	E(lx)	D(m)
1	4889	0.57
2	1222	1.15
3	543	1.72
4	306	2.29
5	196	2.87

Luminous flux luminaire
1654 lm


Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable DALI		

Physical

Color	White	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	62		
Weight (kg)	1.36		
Tilt (°)	90		

Certification / Marking



UT Spot Ceiling Ø86 Dali Version



Holding ring
08.8410.00

Screening crosspiece
08.8411.00