

## UT Spot Track Multichip Ø 86

09.4983.30 - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	Net lumen (lm)	776
Lamp category	LED	Mountings	Track
Power (W)	11.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

### Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Super spot
Beam angle (°)	8
Beam angle C90-270 (°)	8



Beam Angle:	8°		
	h(m)	E(lx)	D(m)
1	20322	0.14	
2	5081	0.27	
3	2258	0.41	
4	1270	0.54	
5	813	0.68	

Luminous flux luminaire  
776 lm

### Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

### Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.18
Tilt (°)	90
Rotation (°)	360

### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.