



## UT Spot Track Multichip Ø 86

■ 09.4984.30 - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	687
Power (W)	11.5W	Mountings	Track
System power (W)	11.5	Environment	Indoor dry location
CCT (K)	3000K		

### Optical


Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Super spot
Beam angle (°)	8
Beam angle C90-270 (°)	8



Beam Angle: 8°

h(m)	E(lx)	D(m)
1	17976	0.14
2	4494	0.27
3	1997	0.41
4	1124	0.54
5	719	0.68

Luminous flux luminaire  
687 lm



### Electrical

Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	220-240V	Emergency	Without
Current (mA)	1050	Insulation class	II
Dimmable	No		
Driver	Integrated		

### Physical

Color	White	Spot diameter (mm)	86
Orientation	Adjustable		
Weight (kg)	0.74		
Tilt (°)	90		
Rotation (°)	360		

### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

