

## UT Spot Track Multichip Ø 86 Dali Version

09.4981.30.DA - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	687
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	11.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Super spot
<b>Beam angle (°)</b>	8
<b>Beam angle C90-270 (°)</b>	8



Beam Angle: 8°

	h(m)	E(lx)	D(m)
1	17976	0.14	
2	4494	0.27	
3	1997	0.41	
4	1124	0.54	
5	719	0.68	

Luminous flux luminaire  
687 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmable DALI		
	1		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.18
<b>Tilt (°)</b>	90
<b>Rotation (°)</b>	360

### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.