



UT Spot Track Multichip Ø 86 Dali Version

■ 09.4982.14.DA - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 807 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 11.5W | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 80 | | |

Optical


| | |
|-------------------------------|------------|
| Lighting type | Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Super spot |
| Beam angle (°) | 8 |
| Beam angle C90-270 (°) | 8 |



Beam Angle: 8°

| | h(m) | E(lx) | D(m) |
|---|-------|-------|------|
| 1 | 21128 | 0.14 | |
| 2 | 5282 | 0.27 | |
| 3 | 2348 | 0.41 | |
| 4 | 1321 | 0.54 | |
| 5 | 845 | 0.68 | |

Luminous flux luminaire
807 lm



Electrical

| | | | |
|-----------------------|---------------|-------------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |
| Emergency | Without | | |

Physical

| | |
|---------------------|------------|
| Color | Black |
| Orientation | Adjustable |
| Weight (kg) | 1.18 |
| Tilt (°) | 90 |
| Rotation (°) | 360 |

Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.

