



UT Spot Track Multichip Ø 86 On Board Dimmer Included

■ 09.4982.14 - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	Net lumen (lm)	807
Lamp category	LED	Mountings	Track
Power (W)	11.5W	Environment	Indoor
CCT (K)	4000K		
CRI	80		


Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Super spot
Beam angle (°)	8
Beam angle C90-270 (°)	8



Beam Angle:	8°		
	h(m)	E(lx)	D(m)
1	21128	0.14	
2	5282	0.27	
3	2348	0.41	
4	1321	0.54	
5	845	0.68	

Luminous flux luminaire
807 lm



Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable		
Emergency	Without		

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	1.18
Tilt (°)	90
Rotation (°)	360

Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

