



## UT Spot Track Multichip Ø86

09.4985.30 - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 807    |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 11.5W | Environment    | Indoor |
| CCT (K)         | 4000K |                |        |
| CRI             | 80    |                |        |

### Optical


|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | Top LED    |
| Light distribution     | Symmetric  |
| Optical type           | Super spot |
| Beam angle (°)         | 8          |
| Beam angle C90-270 (°) | 8          |



Beam Angle: 8°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 21128 | 0.14 |
| 2    | 5282  | 0.27 |
| 3    | 2348  | 0.41 |
| 4    | 1321  | 0.54 |
| 5    | 845   | 0.68 |

Luminous flux luminaire  
807 lm




### Electrical

|                |            |                  |    |
|----------------|------------|------------------|----|
| Frequency (Hz) | 50/60      | Insulation class | II |
| Dimmable       | No         |                  |    |
| Driver         | Integrated |                  |    |
| Driver type    | Electronic |                  |    |
| Emergency      | Without    |                  |    |

### Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 1.18       |
| Tilt (°)     | 90         |
| Rotation (°) | 360        |

### Certification / Marking



### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.