

UT Spot Track Multichip Ø86 On Board Dimmer Included

09.4981.30 - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 687 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 11.5W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|------------|
| Lighting type | Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Super spot |
| Beam angle (°) | 8 |
| Beam angle C90-270 (°) | 8 |



Beam Angle: 8°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 17976 | 0.14 |
| 2 | 4494 | 0.27 |
| 3 | 1997 | 0.41 |
| 4 | 1124 | 0.54 |
| 5 | 719 | 0.68 |

Luminous flux luminaire
687 lm


Electrical

| | | | |
|----------------|------------------------|------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Electronic dimmable | | |
| Emergency | Without | | |

Physical

| | |
|--------------|------------|
| Color | White |
| Orientation | Adjustable |
| Weight (kg) | 1.18 |
| Tilt (°) | 90 |
| Rotation (°) | 360 |

Certification / Marking



Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.