

UT Spot Track Ø 57

09.4480.30A - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	Net lumen (lm)	1255
Lamp category	LED	Mountings	Track
Power (W)	23.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	21
Beam angle C90-270 (°)	21



Beam Angle: 13°

	h(m)	E(lx)	D(m)
1	19095	0.22	
2	4774	0.44	
3	2122	0.66	
4	1193	0.88	
5	764	1.10	

Luminous flux luminaire
2007 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	0.57
Tilt (°)	90
Rotation (°)	360



Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø 57



Honeycomb
08.8428.00



Snoot shielding cone
08.0526.40



Screening crosspiece
08.8429.00



Snoot shielding cone
08.0526.BW



Flood lens
08.8432.00



Snoot shielding cone
08.0526.00



Elliptical lens
08.8431.00