



## UT Spot Track Ø 57

■ 09.4483.30A - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1033
Power (W)	23.2	Mountings	Track
System power (W)	23.2	Environment	Indoor dry location
CCT (K)	4000K		

### Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	21
Beam angle C90-270 (°)	21



Beam Angle: 21°

h(m)	E(lx)	D(m)
1	5683	0.37
2	1421	0.73
3	631	1.10
4	355	1.47
5	227	1.83

Luminous flux luminaire  
1033 lm




### Electrical

Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	220-240V	Emergency	Without
Current (mA)	550	Insulation class	II
Dimmable	No		
Driver	Integrated		

### Physical

Color	White	Spot diameter (mm)	57
Orientation	Adjustable		
Weight (kg)	0.57		
Tilt (°)	90		
Rotation (°)	360		



### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø 57



---

Snoot shielding cone  
08.0526.00



---

Screening crosspiece  
08.8429.00



---

Snoot shielding cone  
08.0526.BW




---

Honeycomb  
08.8428.00



---

Snoot shielding cone  
08.0526.40



---

Elliptical lens  
08.8431.00



---

Flood lens  
08.8432.00