



## UT Spot Track Ø 57 GA

■ 09.7700.14A - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1255
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	23.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	10
<b>Beam angle C90-270 (°)</b>	10



Beam Angle: 10°

	h(m)	E(lx)	D(m)
1	1.15	14650	0.18
2	2	3662	0.36
3	3	1628	0.54
4	4	916	0.72
5	5	586	0.90

Luminous flux luminaire  
1255 lm




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black	<b>Spot diameter (mm)</b>	57
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	0.57		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		



### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.



## UT Spot Track Ø 57 GA



---

Snoot shielding cone  
08.0526.00



---

Elliptical lens  
08.8431.00



---

Snoot shielding cone  
08.0526.BW



---

Flood lens  
08.8432.00



---

Honeycomb  
08.8428.00



---

Snoot shielding cone  
08.0526.40



---

Screening crosspiece  
08.8429.00