



## UT Spot Track Ø 57 GA All White

■ 09.7708.30A78 - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 1108                |
| Power (W)        | 23.5W | Mountings      | Track               |
| System power (W) | 23.2  | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 42        |
| Beam angle C90-270 (°) | 42        |



Beam Angle: 42°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2623  | 0.76 |
| 2    | 656   | 1.52 |
| 3    | 291   | 2.28 |
| 4    | 164   | 3.05 |
| 5    | 105   | 3.81 |

Luminous flux luminaire  
1108 lm



### Electrical



|                |            |                  |              |
|----------------|------------|------------------|--------------|
| Frequency (Hz) | 50/60      | Driver type      | Non Dimmable |
| Voltage (V)    | 220-240V   | Emergency        | Without      |
| Current (mA)   | 550        | Insulation class | II           |
| Dimmable       | No         |                  |              |
| Driver         | Integrated |                  |              |

### Physical

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | White      | Spot diameter (mm) | 57 |
| Orientation  | Adjustable |                    |    |
| Weight (kg)  | 0.57       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.



UT Spot Track Ø 57 GA All White



---


Snoot shielding cone  
08.0526.40

---

Snoot shielding cone  
08.0526.00

---

Screening crosspiece  
08.8429.00



---

Snoot shielding cone  
08.0526.BW

---

Honeycomb  
08.8428.00

---

Elliptical lens  
08.8431.00



---

Flood lens  
08.8432.00