

UT Spot Track Ø 57 On Board Dimmer Included

09.4450.30A - White

Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	**CRI**	90
Lamp category	LED	**Net lumen (lm)**	1094
Power (W)	23.2	**Mountings**	Track
System power (W)	23.2	**Environment**	Indoor dry location
CCT (K)	4000K		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Luminous flux luminaire
1094 lm

Beam Angle: 10°

h(m)	E(lx)	D(m)
1	12780	0.18
2	3195	0.36
3	1420	0.54
4	799	0.72
5	511	0.90

Electrical

Frequency (Hz)	50/60	**Driver type**	Dimmer on board
Voltage (V)	220-240V	**Emergency**	Without
Current (mA)	550	**Insulation class**	II
Dimmable	Yes		
Driver	Integrated		

Physical

Color	White	**Spot diameter (mm)**	57
Orientation	Adjustable		
Weight (kg)	0.57		
Tilt (°)	90		
Rotation (°)	360		

Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø 57 On Board Dimmer Included

Elliptical lens
08.8431.00

Snoot shielding cone
08.0526.BW

Snoot shielding cone
08.0526.40

Screening crosspiece
08.8429.00

Flood lens
08.8432.00

Honeycomb
08.8428.00

Snoot shielding cone
08.0526.00