

UT Spot Track Ø 57 On Board Dimmer Included

09.4450.30A - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	Net lumen (lm)	1094
Lamp category	LED	Mountings	Track
Power (W)	23.5W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Beam Angle:	10°		
	h(m)	E(lx)	D(m)
1	12780	0.18	
2	3195	0.36	
3	1420	0.54	
4	799	0.72	
5	511	0.90	

Luminous flux luminaire
1094 lm

Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		
Emergency	Without		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	0.57
Tilt (°)	90
Rotation (°)	360

Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø 57 On Board Dimmer Included



Flood lens
08.8432.00



Snoot shielding cone
08.0526.BW



Screening crosspiece
08.8429.00



Elliptical lens
08.8431.00



Honeycomb
08.8428.00



Snoot shielding cone
08.0526.00



Snoot shielding cone
08.0526.40