

## UT Spot Track Ø 86

■ 09.4283.14A - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	Net lumen (lm)	2363
Lamp category	LED	Mountings	Track
Power (W)	29.3W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

### Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	23
Beam angle C90-270 (°)	23



Beam Angle:	23°		
	h(m)	E(lx)	D(m)
1	11140	0.41	
2	2785	0.81	
3	1238	1.22	
4	696	1.63	
5	446	2.03	

Luminous flux luminaire  
2363 lm

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220	Insulation class	II
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

### Physical

Color	Black	Spot diameter (mm)	86
Orientation	Adjustable		
Weight (kg)	1.36		
Tilt (°)	90		
Rotation (°)	360		

### Note


FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

## UT Spot Track Ø 86



---

Screening crosspiece  
08.8411.00



---

Holding ring  
08.8410.00