

## UT Spot Track Ø 86

■ 09.4285.14 - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	Net lumen (lm)	1947
Lamp category	LED	Mountings	Track
Power (W)	29.3W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

### Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	32
Beam angle C90-270 (°)	32



Beam Angle: 32°

h(m)	E(lx)	D(m)
1	5719	0.58
2	1430	1.15
3	635	1.73
4	357	2.31
5	229	2.89

Luminous flux luminaire  
1947 lm

### Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		


### Physical

Color	Black
Orientation	Adjustable
Weight (kg)	1.36
Tilt (°)	90
Rotation (°)	360

### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

## UT Spot Track Ø 86



---

Holding ring  
08.8410.00



---

Screening crosspiece  
08.8411.00